

**CODE NUMBER**

2102469IN

**DESCRIPTION**

Vitreous China Wall-Mounted Water Closet.

**DETAILS**

- Flush Volume: 4.2–6.0 Lpf (1.1–1.6 gpf)
- Flush volume determined by the flushometer used with the fixture
- Rim Height: 13 1/4"–17" (337–432mm)
- Nominal Dimensions: 26 3/4" x 15" x 16 3/4" (679 x 381 x 425mm)

**FEATURES**

- White Vitreous China
- Elongated bowl
- Wall mounted, wall outlet
- Siphon jet flushing action
- Static load rating of 750 lbs (see Notes)
- 1 1/2 I.P.S. rear spud inlet
- 2 1/8" fully glazed trapway
- Toilet seat and mounting kit needs to be bought separately

**PLUMBING SYSTEM REQUIREMENTS**

- Minimum Flowing Pressure: 25 PSI (172 kPa)
- Maximum Static Pressure: 80 PSI (552 kPa)

**COMPLIANCES & CERTIFICATIONS**

(ADA Compliant, BREEAM Materials Credit, CalGreen Compliant, CEC Compliant, cUPC Green Certified, EPD, Green Globes Materials & Resources Credit, HPD, LEED Materials & Resources EPD Credit, LEED Materials & Resources HPD Credit, Satisfies LEED Credits, WaterSense Listed, WELL Building Standard)

**NOTES**

All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

**ROUGH-IN**

