

CODE NUMBER

TRF-1036-D25 & TRF-1000-RG

DESCRIPTION

TruFlush Concealed Manual Dual Flushometer with 25mm Valve Body and Wall Plate in Rose Gold Finish for Water Closet.

COMPOSITION

- Valve Body: 34000036 (TRF-1036-D25)
- Wall Plate: 34000032 (TRF-1000-RG)

DETAILS

- Full Flush Volume: 6.0 Lpf (1.6 gpf)
- Half Flush Volume: 3.0 Lpf (0.8 gpf)
- Wall Plate Finish: Rose Gold (RG)
- Valve: Piston
- Valve Body Material: Yellow Brass
- Bypass: Filtered
- Fixture Type: Water Closet
- Fixture Connection: Rear Spud

FEATURES

- Rose Gold finish, corrosion-resistant, vandal resistant metal wall plate
- Easy to push manual button is ADA compliant - less than 5 lbf/22N of force required to activate
- Accurate flush volume
- Heavy duty brass valve body
- Piston color-coded by flush volume for easy identification
- Replaceable piston assembly, accessible by removing front wall plate
- Concealed shut-off sleeve adjusts flow rate
- Safety collar locks activation assembly to prevent access of internal components without shutting off water
- Fixed Volume Piston with Filtered O-ring Bypass
- Aspirator technology reduces noise post flushing
- Inlet: G1" (25mm)
- Outlet: 1-1/2" NPSM (40mm)
- Valve Body & Manual Wall Plate are sold separately


COMPLIANCES & CERTIFICATIONS


(ADA Compliant, UPC-I)

RECOMMENDED SPECIFICATION

Valve shall be concealed with front access wall plate smaller than 7" x 7" and shall have integrated control stop.


VALVE OPERATING PRESSURE (FLOWING)

20-80 PSI (138-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

NOTES

All information contained within this document subject to change without notice.

ROUGH-IN



NOTE : Flush Connections shown in dotted lines not included.

