

INSTALLATION INSTRUCTIONS FOR WALL HUNG WATER CLOSET

BEFORE YOU BEGIN



WARNING: Risk of personal injury or product damage. Handle with care.

- Vitreous China can break or chip if the bolts and nuts are over-tightened, or if the product is handled carelessly.
- Observe all local plumbing and building codes.
- Carefully inspect the new toilet for any damage.
- If the In-wall tank is not installed, refer to the manufacturer's instructions before installation.

- ✓ Minimum Flowing Pressure: 25 PSI
- ✓ Minimum Flow Rate: 68 LPM
- ✓ Maximum Static Pressure: 70 PSI before installation.

FOR BEST PERFORMANCE OF YOUR SLOAN WATER CLOSET, USE SLOAN® TRUFLUSH FLUSHOMETERS



RECOMMENDED TOOLS AND MATERIALS: -



Putty Knife




Adjustable Wrench



Level



Silicone



Hacksaw



Tape Measure



Pipe Wrench




Drill



Channel Lock Pliers



Phillips Screwdriver


















Regular Screwdriver

INSTALLATION GUIDELINE - For Exposed Mounting Water Closet

1 Cut bolts if needed. File bolt ends.	2 Remove Inlet Plug.	3 Slide the gaskets on the Inlet & Outlet pipe as shown.	4 Slide the inlet pipe into the wall openings at water inlet to test the fitment of inlet pipe with toilet.	5 Note the distance between the wall & the toilet at the location shown. Measure excess length "A" on the inlet pipe.
6 Remove the toilet. Cut & file the inlet pipe to proper length by removing excess length "A".	7 Slide the outlet pipe into the wall openings at waste outlet to test the fitment of outlet pipe with toilet.	8 Note the distance between the wall & the toilet at the location shown. Measure excess length "B" of the outlet pipe.	9 Remove the toilet. Cut & file the outlet pipe to proper length by removing excess length "B".	10 Add silicon sealant to the gasket grooves.
11 Mount the toilet on the projected studs.	12 Level the toilet with Spirit level.	13 Insert rubber, washer & fixing nut for securing the toilet with the wall. Cut the extra length of the stud projecting out. Place the plastic caps.	14 Flush the toilet. Check for leaks. Seal connections if required.	15 Seal around the edges. Do not use cement.

















Note: Product illustrations shown are representative only; actual products may vary.

INSTALLATION GUIDELINE - For Lateral Anchored Water Closet

1 Cut bolts if needed. File bolt ends. 	2 Mount the sleeve on the bolts and remove inlet plug. 	3 If connector is not already installed, apply Teflon tape on the connector & install. 	4 Slide on the gaskets as shown. 
5 Install the accessory kit into the installation hole of the toilet. 	6 Slide the inlet pipe into the wall openings for waste pipe. Test fit the toilet. 	7 Note the distance between the wall and the toilet at the location shown. Measure excess length "A" for the inlet pipe. 	8 Cut and file the inlet pipe to the proper length by removing excess length "A". 
9 Slide the outlet pipe into the wall openings for waste pipe. Test fit the toilet. 	10 Note the distance between the wall and the toilet at the location shown. Measure excess length "B" for the outlet pipe. 	11 Cut and file the outlet pipe to the proper length by removing excess length "B". 	12 Add silicon sealant to the gasket grooves. 
13 Mount the toilet on the wall. 	14 Level the toilet and tighten accessories using Allen key. Close the installation holes using the caps. 	15 Flush the toilet. Check for leaks. Seal connections if required. 	16 Seal around the edges. Do not use cement. 

Note: Product illustrations shown are representative only; actual products may vary.

INSTALLATION GUIDELINE - For Concealed/ Blind Installation Water Closet

1 Cut bolts if needed. File bolt ends. 	2 Mount the sleeve on the bolts and remove inlet plug. 	3 If connector is not already installed, apply Teflon tape on the connector & install. 	4 Slide on the gaskets as shown. 
5 WC mounting holder comes in installed condition in WC mounting holes 	6 Slide the inlet pipe into the wall openings for waste pipe. 	7 Note the distance between the wall and the toilet at the location shown. Measure excess length "A" for the inlet pipe. 	8 Cut and file the inlet pipe to the proper length by removing excess length "A". 
9 Slide the outlet pipe into the wall openings for waste pipe. Test fit the toilet. 	10 Note the distance between the wall and the toilet at the location shown. Measure excess length "B" for the outlet pipe. 	11 Cut and file the outlet pipe to the proper length by removing excess length "B". 	12 Add silicon sealant in the gasket grooves. 
13 Mount the toilet on the wall. 	14 Level the toilet and tighten accessories using allen key through seat mounting holes. 	15 Flush the toilet. Check for leaks. Seal connections if required. 	16 Seal around the edges. Do not use cement. 

Note: Product illustrations shown are representative only; actual products may vary.

SLOAN® INDIA PRIVATE LIMITED — LIMITED WARRANTY SUMMARY

Sloan India private limited ("Sloan"), warrants its products against defects in materials and workmanship, excluding damage caused by matters beyond Sloan's reasonable Control. Instructions for filing claims can be found in the limited warranty which can be obtained at <https://www.sloan.com/company/international/sloanindia> or by requesting a Free copy by telephone to Sloan India toll free number 1 800 123 3080 or via mobile: +91 729 005 0961. Sloan will repair or replace your Defective product, or provide a refund, as your exclusive remedy.

This is only a general summary of Sloan's limited warranty, so it is important to note that the specific terms, conditions, limitations and exclusions, including the duration of Warranty coverage for your Sloan product, are contained in the actual Sloan limited warranty. The limited warranty is subject to applicable laws in your country, state, Province or other jurisdiction—and disputes arising under the limited warranty are to be resolved by binding arbitration unless you provide Sloan with an opt-out notice no later Than 30 days after your purchase date. In case of a conflict with this summary, the terms and conditions set forth in the complete limited warranty will prevail.

The information contained in this document is subject to change without notice.

SLOAN INDIA PRIVATE LIMITED • 344, PHASE-II UDYOG VIHAR, GURUGRAM 122015 INDIA

Phone: (+91) 124-4908587/88 • Toll Free: 1800.123.3080 • customercare@sloan.in • www.sloan.in